





EC-E-3 : 3 flute, 38°helix medium length solid carbide endmills.



Designation	D	d	ap	L	Flute	Ha°/b>	Rd°/b>	Shank	fz(min)	fz(max)	Grade
EC010E025-3C03	1.00	3.00	2.50	38.00	3	38.0	5.0	C	0.01	0.01	IC300IC900
EC015E04-3C04	1.50	4.00	4.00	50.00	3	38.0	5.0	C	0.01	0.02	IC300IC900
EC025E07-3C03	2.50	3.00	7.00	38.00	3	38.0	5.0	C	0.01	0.03	IC900
EC030E10-3C03	3.00	3.00	10.00	38.00	3	38.0	5.0	C	0.01	0.04	IC08IC300IC900
EC030E10-3C06	3.00	6.00	10.00	57.00	3	38.0	5.0	C	0.01	0.04	IC300IC900
EC035E12-3C04	3.50	4.00	12.00	50.00	3	38.0	5.0	C	0.01	0.04	IC08IC300IC900
EC040E12-3C04	4.00	4.00	12.00	50.00	3	38.0	5.0	C	0.02	0.05	IC08IC300IC900
EC040E12-3C06	4.00	6.00	12.00	57.00	3	38.0	5.0	C	0.02	0.05	IC900
EC045E14-3C06	4.50	6.00	14.00	57.00	3	38.0	5.0	C	0.02	0.05	IC08IC300IC900
EC050E14-3C05	5.00	5.00	14.00	50.00	3	38.0	5.0	C	0.02	0.06	IC08IC300IC900
EC050E14-3C06	5.00	6.00	14.00	57.00	3	38.0	5.0	C	0.02	0.06	IC900
EC050E14-3W06	5.00	6.00	14.00	57.00	3	38.0	5.0	W	0.02	0.06	IC900
EC060E16-3C06	6.00	6.00	16.00	57.00	3	38.0	5.0	C	0.03	0.07	IC08IC300IC900
EC060E16-3W06	6.00	6.00	16.00	57.00	3	38.0	5.0	W	0.03	0.07	IC900
EC070E20-3C07	7.00	7.00	20.00	60.00	3	38.0	5.0	C	0.03	0.08	IC08IC300IC900
EC080E20-3C08	8.00	8.00	20.00	63.00	3	38.0	5.0	C	0.03	0.09	IC08IC300IC900
EC080E20-3W08	8.00	8.00	20.00	63.00	3	38.0	5.0	W	0.03	0.09	IC300IC900
EC100E22-3C10	10.00	10.00	22.00	72.00	3	38.0	5.0	C	0.03	0.10	IC08IC300IC900

EC100E22-3W10	10.00	10.00	22.00	72.00	3	38.0	5.0	W	0.03	0.10	IC300IC900
EC120E25-3C12	12.00	12.00	25.00	73.00	3	38.0	5.0	C	0.04	0.11	IC08IC300IC900
EC120E25-3W12	12.00	12.00	25.00	83.00	3	38.0	5.0	W	0.04	0.11	IC300IC900
EC140E25-3C14	14.00	14.00	25.00	83.00	3	38.0	5.0	C	0.04	0.12	IC900
EC140E25-3W14	14.00	14.00	25.00	83.00	3	38.0	5.0	W	0.04	0.12	IC900
EC140E32-3C14	14.00	14.00	32.00	83.00	3	38.0	5.0	C	0.04	0.12	IC300
EC160E32-3C16	16.00	16.00	32.00	92.00	3	38.0	5.0	C	0.05	0.13	IC08IC300IC900
EC160E32-3W16	16.00	16.00	32.00	92.00	3	38.0	5.0	W	0.05	0.13	IC900
EC180E32-3C18	18.00	18.00	32.00	92.00	3	38.0	5.0	C	0.05	0.13	IC300IC900
EC180E32-3W18	18.00	18.00	32.00	92.00	3	38.0	5.0	W	0.05	0.13	IC900
EC200E38-3C20	20.00	20.00	38.00	104.00	3	38.0	5.0	C	0.05	0.13	IC300IC900
EC200E38-3W20	20.00	20.00	38.00	104.00	3	38.0	5.0	W	0.05	0.13	IC300IC900

Multi-purpose endmill.
Suitable for deep slotting.