







TGSF : TANGSLIT slitting cutters with TANG-GRIP inserts.



| Designation | W | D | Z | A | Da | Tmax | RPM max | a°/b> | D3 | A2 | SS | CSI |
|-----------------|------|--------|----|------|-------|-------|---------|-------|-------|-----|---------|---------|
| TGSF 50-2-8KR | 2.00 | 50.00 | 5 | 1.65 | 8.00 | 10.00 | 1600 | 90 | 28.00 | 2.5 | - | - |
| TGSF 63-2-10KR | 2.00 | 63.00 | 6 | 1.65 | 10.00 | 14.50 | 1260 | 90 | 32.00 | 2.5 | - | - |
| TGSF 80-2-22KR | 2.00 | 80.00 | 8 | 1.65 | 22.00 | 19.00 | 1000 | 90 | 40.00 | 2.5 | - | - |
| TGSF 100-2-22KR | 2.00 | 100.00 | 11 | 1.65 | 22.00 | 29.00 | 800 | 90 | 40.00 | 2.5 | - | - |
| TGSF 125-2-32KR | 2.00 | 125.00 | 13 | 1.65 | 22.00 | 34.00 | 640 | 90 | 55.00 | 2.5 | - | - |
| TGSF 50-3-8K | 3.00 | 50.00 | 4 | 2.50 | 8.00 | 10.00 | 6300 | 90 | - | - | - | - |
| TGSF 63-3-10K | 3.00 | 63.00 | 5 | 2.50 | 10.00 | 14.50 | 5000 | 90 | - | - | - | - |
| TGSF 80-3-22K | 3.00 | 80.00 | 7 | 2.50 | 22.00 | 19.00 | 3900 | 90 | - | - | - | - |
| TGSF 100-3-22K | 3.00 | 100.00 | 8 | 2.50 | 22.00 | 29.00 | 4470 | 90 | - | - | SW32-40 | R 22-46 |
| TGSF 125-3-32K | 3.00 | 125.00 | 10 | 2.50 | 32.00 | 34.00 | 3820 | 90 | - | - | S32-55 | R 32-55 |
| TGSF 160-3-32K | 3.00 | 160.00 | 12 | 2.50 | 32.00 | 52.00 | 3000 | 90 | - | - | S32-55 | R 32-55 |
| TGSF 63-4-10K | 4.00 | 63.00 | - | - | 10.00 | - | 5000 | 90 | - | - | - | - |
| TGSF 80-4-22K | 4.00 | 80.00 | - | - | 22.00 | - | 3900 | 90 | - | - | - | - |
| TGSF 100-4-22K | 4.00 | 100.00 | 8 | 3.30 | 22.00 | 29.00 | 6000 | 90 | - | - | SW32-40 | R 22-46 |
| TGSF 125-4-32K | 4.00 | 125.00 | 10 | 3.30 | 32.00 | 34.00 | 3800 | 90 | - | - | S32-55 | R 32-55 |
| TGSF 160-4-40K | 4.00 | 160.00 | 12 | 3.30 | 40.00 | 39.00 | 3000 | 90 | - | - | S40-80 | R 40-80 |

ETG extractor should be ordered separately.
For drive flange set dimensions, refer to "Related Holder"