




PICCO R/L 004-007 (Radius) : Inserts featuring full radius for internal boring and profiling from 4.0 mm.



Designation	d	W?.05	f	a	R	l1	l2	Tmax-r	D min	Grade
PICCO R 004.0.50-16	4	1	1.5	3.5	0.5	30	15	0.8	4	IC228
PICCO L 004.0.50-16	4	1	1.5	3.5	0.5	30	15	0.8	4	IC228
PICCO R 005.0.50-20	5	1	1.9	4.4	0.5	35	19	1	5	IC228
PICCO L 005.0.50-20	5	1	1.9	4.4	0.5	35	19	1	5	IC228
PICCO R 005.0.75-20	5	1.5	1.9	4.4	0.75	35	19	1	5	IC228
PICCO L 005.0.75-20	5	1.5	1.9	4.4	0.75	35	19	1	5	IC228
PICCO R 005.1.00-20	5	2	1.9	4.4	1	35	19	1	5	IC228
PICCO L 005.1.00-20	5	2	1.9	4.4	1	35	19	1	5	IC228
PICCO R 006.0.50-25	6	1	2.3	5.3	0.5	40	24	1.8	6	IC228
PICCO L 006.0.50-25	6	1	2.3	5.3	0.5	40	24	1.8	6	IC228
PICCO R 006.0.75-25	6	1.5	2.3	5.3	0.75	40	24	1.8	6	IC228
PICCO L 006.0.75-25	6	1.5	2.3	5.3	0.75	40	24	1.8	6	IC228
PICCO R 006.1.00-25	6	2	2.3	5.3	1	40	24	1.8	6	IC228
PICCO L 006.1.00-25	6	2	2.3	5.3	1	40	24	1.8	6	IC228
PICCO R 007.0.50-30	7	1	2.8	6.3	0.5	45	29	2.5	6.8	IC228
PICCO L 007.0.50-30	7	1	2.8	6.3	0.5	45	29	2.5	6.8	IC228
PICCO R 007.0.75-30	7	1.5	2.8	6.3	0.75	45	29	2.5	6.8	IC228
PICCO L 007.0.75-30	7	1.5	2.8	6.3	0.75	45	29	2.5	6.8	IC228
PICCO R 007.1.00-30	7	2	2.8	6.3	1	45	29	2.5	6.8	IC228
PICCO L 007.1.00-30	7	2	2.8	6.3	1	45	29	2.5	6.8	IC228